



Electrolux Professional Line 5000

The all-in-one business solution for your laundry

We feature our most energy efficient washer and dryer models in PLUS.

High-Spin "H" Models

Electrolux 400-450G soft-mount washers remove more water, minimizing dry time and providing significant gas savings. Installs on wood floors, upper levels, & over basements!

Soft-Mount Benefits:

- Highest level of water removal at end of cycle providing for fastest possible drying time and lowest possible energy costs.
- AWS – Automatic Water Savings:
 - Save up to 30% on water with AWS, automatically. With every wash cycle, AWS determines the actual weight of the load and adds precisely the right amount of water significantly reducing water consumption and energy costs.
- Smart Dosing System:
 - Compatible with Smart Dosing software which adjusts the chemical levels in relation to the AWS water adjustments to ensure the proper amount of water to chemical ratio.
- Power Balance:
 - Power Balance is an industry exclusive measurement of spin speed to load size that ensures optimal water removal for every load. It measures constantly during final extraction, while competitive models measure for only a short time. It is proven to remove more water and further reduce drying time and related drying costs.



Available in 30, 45, 60, and 75 lb. capacities. Stainless steel front panel, standard. Designed to save water and energy and achieve impressive Modified Energy Factor (MEF) results.

Single Pocket Dryers

Use up to 25% less gas and dry 12% faster. Electrolux dryers feature, increased load capacities, faster drying, less wear-and-tear on garments, lower energy consumption, and time savings.

Dryer Benefits:

- Dries 12% faster, saving 25% in gas
- Axial airflow and tight construction for extremely low energy consumption
- Reversing drums (standard) for even greater savings. Reduces energy consumption, prevents tangling and linens dry more quickly
- Residual Moisture Control:
 - An innovative sensor automatically stops the dryer precisely when the linens are dry. Eliminating human error. You'll benefit from longer linen life and significant labor and energy savings. Less wear-and-tear on garments and prevents over-drying
- Best lint screen in the industry - easiest to clean, ergonomically designed
- Large door opening for easy loading and unloading
- Reversible door
- 120 volt, single-phase for easy installation

Electrolux washers & dryers are the only true green solution for your laundry room.



Available in 35x35 and 50x50 Stack, 35, 67, 83, and 100 lb. capacities. Vertical blue wave front panel standard.



Electrolux Soft-Mount 400-450G Washers	W5130H		W5180H		W5240H		W5300H	
Capacity (lbs/kg)	30	14	45	20	60	27	75	33
Width (in/mm) *with optional soap injector	35 13/16	910	38 3/16	970	40 3/16	1020	40 3/16	1020
Depth Overall (in/mm) *with optional soap injector	32 1/2	825	37 3/16	945	39	990	44 11/16	1135
Tilting Depth Overall (in/mm)	n/a							
Height (in/mm)	52 3/16	1325	55 1/2	1410	56 7/8	1445	56 7/8	1445
Tilted Height (in/mm)	n/a							
Height to Bottom of Door (in/mm)	17 1/8	435	18 1/2	470	19 11/16	500	19 11/16	500
Door Opening Diameter (in/mm)	15 9/16	395	17 1/8	435	17 1/8	435	17 1/8	435
Cylinder Volume (ft3/l)	4.6	130	6.4	180	8.5	240	10.6	300
Max Floor Load during Extract (lbs/kN)	697 +/- 112	3.1 +/- 0.5	944 +/- 224	4.2 +/- 1.0	1169 +/- 224	5.2 +/- 1.0	1236 +/- 292	5.5 +/- 1.3
Frequency of Dynamic Force (Hz)	18.6		17.6		16.8		15.8	
Crated Weight (lbs/kg)	625	284	827	376	986	448	1162	528
Operating Speeds								
Wash (rpm)	44		44		40		40	
Max Extract (rpm/g-factor)	1115 / 450		1055 / 450		1005/450		950/400	
Electrical Requirements								
Voltage/Frequency/Phase	208 - 240/60/1 or 3~				208 - 240/60/3~			
Power(kW)/Full Load Current (Amps) /Ckt Breaker (Amps)	1.3 / 5.8 / 15		2.4 / 11.2 / 15		2.4 / 13.2 / 20		2.4/9.2/15	
Water Information								
Inlet Fittings (* = 3 Inlet Fittings)	3/4*	DN20	3/4*	DN20	3/4*	DN20	3/4*	DN20*
Flow Each Inlet @ 45 psi (gpm/lpm)	5	20	16	60	16	60	16	60
Recommended Water Pressure (psi/kPa)	30 - 90	200 - 600	30 - 90	200 - 600	30 - 90	200 - 600	30 - 90	200 - 600
Drain Outlet Diameter (in/mm)	3	75	3	75	3	75	3	75
Max Drain Flow (gpm/lpm)	40	150	40	150	40	150	40	150
Steam Supply* (psi/kPa)	40 - 50	275-350	40 - 50	275-350	40 - 50	275-350	40 - 50	275-350
Steam Inlet*	1/2	DN15	1/2	DN15	1/2	DN15	1/2	DN15
Heating Alternatives								
Electric	Contact Laundrylux for heating power & voltage options							
Direct Steam	Option							

Electrolux Dryer Models	T5290		T5550		T5675	
Capacity (lb/kg)	35	15.9	67	30.4	83	37.7
Width (in/mm)	27 15/16	710	37 13/16	960	37 13/16	960
Depth (in/mm)	45 1/2	1155	51 3/4	1315	59 7/16	1510
Depth with door open (in/mm)	68 5/16	1735	83 11/16	2125	91 5/16	2320
Height Overall (in/mm)	65 15/16	1675	73 7/16	1855	73 7/16	1855
Height without heating unit (in/mm)	n/a					
Door opening diameter (in/mm)	22 13/16	580	31 7/8	810	31 7/8	810
Cylinder volume (ft3/l)	10.2	290	19.4	550	23.8	675
Crated Weight (lb/kg)	518	235	717	325	827	375
Utility Connections						
Exhaust duct diameter (in/mm)	8	200	8	250	8	250
Gas connection	1/2 NPT		1/2 NPT		3/4 NPT	
Steam connection, inlet & condensate	1 NPT		1 NPT		1 NPT	
Energy Data						
Gas (Btu/hr)	71,700		112,700		143,400	
Airflow (ft3/min / m3/hr) (gas heat)	360 / 610		550 / 940		670 / 1140	
3000Electric (kW) @ 208-240V/3Ø	13.5 or 18		24 or 32		24 or 32	
Airflow (ft3/min / m3/hr) (elec. heat)	325 / 550		550 / 940		670 / 1140	
Steam (lb/hr / kg/hr) (approximate)	80 / 36		118 / 54		150 / 68	
Airflow (ft3/min / m3/hr) (steam heat)	405 / 690		635 / 1080		810 / 1380	
Electrical Requirements						
Current, gas or steam, 120 V/60Hz (full load/circuit breaker)	7.5A (15A)		12A (20A)		12A (20A)	
Current, gas or steam, 208-240 V/60Hz/1Ø (full load/circuit breaker)	3.5A (15A)		8.5A (15A)		8.5A (15A)	
Current, gas or steam, 208-240 V/60Hz/3Ø (full load/circuit breaker)	3.75A (15A)		10A (15A)		10A (15A)	
Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker)	14.4-18.9 (60A)		26.1-34.4 (110A)		26.1-34.4 (110A)	
Alternate Voltages						
Alternate voltages available. Contact Laundrylux Sales Department for information.						
Supply Pressures						
Natural Gas (inches H2O/mbar)	3.5-10.5/9-26		3.5-10.5/9-26		3.5-10.5/9-26	
Propane (inches H2O/mbar)	8-13 / 20-32		8-13 / 20-32		8-13 / 20-32	
Steam (psi/bar) (max)	145 / 10		145 / 10		145 / 10	
Exhaust back pressure (inches H2O/mbar) (max)	2.2	5.5	2.6	6.48	3	7.5
* For additional sizes please contact a PLUS Representative. Additional sizes available: 35x35 and 50x50 Stacked Dryers.						



PLUS was invented by Pluslux, the leading supplier of professional laundry solutions. With a complete range of Electrolux Professional laundry equipment, Pluslux will create a laundry solution for the specific needs of your business. Healthcare, hospitality, gyms, clubs, salons, restaurants, and all businesses that require professional laundry processing can benefit from the revolutionary Professional Laundry Utility Service.

PLUS technology is patented. All rights reserved.
Copyright 2013. Pluslux and Electrolux are trademarks.

Ease-of-use comes standard with the **New Compass Pro®**

Compass Pro ensures the best utility cost optimization and program flexibility in combination with the market's most user-friendly interface. With large, clear display and intuitive interface simplifying operation, Compass Pro makes for a more user-friendly experience. Users can easily select and navigate the appropriate programs thanks to language selection and voice guidance (optional).

Washer Control

- Flexible and customizable
- Up to 55 programs available of which 15 are programmable
- Large, clear display in more than 20 languages
- Real-time clock for automatic start
- 5 liquid detergent signals for automatic dosing

Dryer Control

- Large display and one control knob for easy program selection
- More than 20 languages available
- Detailed user statistics and programmability
- RMC stops dryer when exact preset moisture level is reached



Longer machine life
with support rollers and advanced blower wheel



Reversing Cylinders
for time & energy savings



Faster Maintenance
with easy to clean lint screen – best in industry

Pluslux LLC
461 Doughty Boulevard • Inwood, NY 11096-1384
(866) 575-1010 • info@plusluxllc.com

www.plusluxllc.com